
## <sup>2023</sup> KLX<sup>®</sup>300SM







## **Front Tire** 110/70-17 **POWER Rear Tire** 130/70-17 Engine 4-stroke single, DOHC, liquid-cooled Single 300mm petal disc with a dual-piston **Front Brakes** caliper Displacement 292cc Single 240mm petal disc with single-piston **Rear Brakes Bore x Stroke** 78.0 x 61.2mm caliper Compression 11.1:1 Ratio DETAILS DFI® with 34mm Keihin throttle body **Fuel System Frame Type** Semi-double cradle Ignition CDI Rake/Trail 25.0°/2.8 in Transmission 6-speed, return shift with wet multi-disc manual clutch orall Longth 86 / in **Final Drive** Chain

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping / 9.1 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1 in

	Overall Length	86.4 IN
	Overall Width	31.1 in
	<b>Overall Height</b>	45.1 in
	Ground Clearance	9.3 in
	Seat Height	33.9 in
	Curb Weight	304.3 lb*
1	Fuel Capacity	2.0 gal
	Wheelbase	56.5 in
	Color Choices	Neon Green, Ebony





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.