## KX<sup>™</sup>450











## **POWER**

**Engine** 4-stroke single, DOHC, liquid-cooled

**Displacement** 449cc

Bore x Stroke 96.0 x 62.1mm

**Compression Ratio** 

12.5:1

Fuel System DFI® with 44mm Keihin throttle body

**Ignition** Digital CDI with three coupler options

Transmission 5-speed, return shift, with wet multi-disc

manual clutch and hydraulic clutch

actuation

Final Drive Chain

**Front Tire** 80/100-21

**Rear Tire** 120/80-19

Front Brakes Single semi-floating 270mm Braking petal

disc with dual-piston caliper

**Rear Brakes** Single 250mm Braking petal disc with

single-piston caliper

## **PERFORMANCE**

Front
Suspension /
Wheel Travel

49mm inverted telescopic coil-spring fork with 16-way compression damping and 16-way rebound damping/12.0 in

Rear Suspension / Wheel Travel Uni-Trak® gas charged shock with piggyback reservoir with dual-range (4 turns stepless high speed/19-way low-speed) compression damping, 22-way rebound damping and adjustable preload/12.1 in

## **DETAILS**

Frame Type Aluminum perimeter

Rake/Trail 27.6°/4.8 in

Overall Length 86.0 in

Overall Width 32.3 in

Overall Height 49.8 in

Ground 13.4 in

Clearance

Seat Height 37.6 in

Curb Weight 233.2 lb\* without fuel / 243.3 lb\*

Fuel Capacity 1.64 gal

Wheelbase 58.5 in

**Color Choices** Lime Green



