
²⁰²³ **KX[™]450SR**







80/100-21

120/80-19

Single semi-floating 270mm. Braking petal

Single 250mm. Braking petal disc with

disc with dual-piston caliper

single-piston caliper

POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	449cc
Bore x Stroke	96.0 x 62.1mm
Compression Ratio	12.5:1
Fuel System	DFI® with 44mm. Keihin throttle body
Ignition	Digital CDI with three coupler options
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain
Electronic Rider Aids	Launch Control Mode

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

	Frame Type	Aluminum perimeter
sc	Rake/Trail	27.6°/4.8 in
	Overall Length	86.0 in
	Overall Width	32.3 in
	Overall Height	49.8 in
	Ground Clearance	13.4 in
	Seat Height	37.6 in
	Curb Weight	233.2 lb* without fuel / 243.3 lb*
	Fuel Capacity	1.64 gal
	Wheelbase	58.5 in
	Color Choices	Lime Green

PERFORMANCE

		0	
Front	12.0 in	Curb Weight	233.2 lb* without fuel / 243.3 l
Suspension / Wheel Travel		Fuel Capacity	1.64 gal
Rear	12.1 in	Wheelbase	58.5 in
Suspension / Wheel Travel		Color Choices	Lime Green





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.