

2023

KX™ 450SR



MSRP
\$12,699



POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	449cc
Bore x Stroke	96.0 x 62.1mm
Compression Ratio	12.5:1
Fuel System	DFI® with 44mm. Keihin throttle body
Ignition	Digital CDI with three coupler options
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain
Electronic Rider Aids	Launch Control Mode

PERFORMANCE

Front Suspension / Wheel Travel	12.0 in
Rear Suspension / Wheel Travel	12.1 in

Front Tire	80/100-21
Rear Tire	120/80-19
Front Brakes	Single semi-floating 270mm. Braking petal disc with dual-piston caliper
Rear Brakes	Single 250mm. Braking petal disc with single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	27.6° / 4.8 in
Overall Length	86.0 in
Overall Width	32.3 in
Overall Height	49.8 in
Ground Clearance	13.4 in
Seat Height	37.6 in
Curb Weight	233.2 lb* without fuel / 243.3 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.5 in
Color Choices	Lime Green

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.