

2023  
KX™ 65



MSRP  
\$3,999



LIME GREEN



POWER

|                   |                                                          |
|-------------------|----------------------------------------------------------|
| Engine            | 2-stroke single, liquid-cooled                           |
| Displacement      | 64cc                                                     |
| Bore x Stroke     | 45.5 x 41.6mm                                            |
| Compression Ratio | 8.4:1                                                    |
| Fuel System       | 24mm Mikuni carburetor                                   |
| Ignition          | CDI with Digital Advance                                 |
| Transmission      | 6-speed, return shift, with wet multi-disc manual clutch |
| Final Drive       | Chain                                                    |

PERFORMANCE

|                                 |                                                                                                                |
|---------------------------------|----------------------------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 33mm leading axle telescopic fork with 4-way rebound damping/8.3 in                                            |
| Rear Suspension / Wheel Travel  | Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in |
| Front Tire                      | 60/100-14                                                                                                      |

|              |                                              |
|--------------|----------------------------------------------|
| Rear Tire    | 80/100-12                                    |
| Front Brakes | Single 180mm disc with single-piston caliper |
| Rear Brakes  | Single 180mm disc with single-piston caliper |

DETAILS

|                  |                                       |
|------------------|---------------------------------------|
| Frame Type       | High-tensile steel semi-double cradle |
| Rake/Trail       | 27° / 2.4 in                          |
| Overall Length   | 62.6 in                               |
| Overall Width    | 29.9 in                               |
| Overall Height   | 37.6 in                               |
| Ground Clearance | 12.0 in                               |
| Seat Height      | 29.9 in                               |
| Curb Weight      | 132.2 lb*                             |
| Fuel Capacity    | 1.0 gal                               |
| Wheelbase        | 44.1 in                               |
| Color Choices    | Lime Green                            |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.