## **MULE PRO-FX™ EPS LE**





MSRP **\$14,899** 



FIRECRACKER RED



## **POWER**

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 75 amp

(max)

Ground Clearance 10.4 in

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

**Fuel Capacity** 

54.1 x 53.3 x 11.0 in

999 lb / 600.0 lb CA Model

Payload Capacity 1,616.3 lb / 1,263.5 for CA Model

Seating Capacity 3

**Towing Capacity** 

2.000 lb

7.9 gal

Lighting

(2) Halogen headlights. (2) LED headlights

## CAPABILITY

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel Double wishbone/8.5 in (L) /8.7 in (R)

Front Tires

26x9.00-12, radial

**Rear Tires** 

26x11.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

**Park Brake Type** 

Independent, Mechanical Disc

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.7 in

Curb Weight 1,832.4 lb\*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type Allo

Additional Features

Roof, Cast Aluminum Wheels

Color Choices Firecracker Red

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.