MULE PRO-FXT™ EPS LE





\$17,299



METALLIC SIERRA BLUE



METALLIC ONYX BLACK



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Rear Tires

Ground Clearance 10.2 in

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH) person)

Cargo Bed Load

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Capacity

Fuel Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

7.9 gal

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Double wishbone/8.7 in Front Suspension / **Wheel Travel**

Rear Suspension / Double wishbone/8.5 (L) /8.7 (R) in **Wheel Travel**

Front Tires 26x9.00-12, radial

26x11.00-12, radial **Steering** Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in

79.5 in **Overall Height**

Curb Weight 1,922.8 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type Alloy

Additional Features Roof

Metallic Onyx Black, Metallic Sierra Blue

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

Color Choices