MULE PRO-MX™ EPS LE





\$14,199



SUPER BLACK



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

102.0 x 85.0 mm **Bore x Stroke**

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft, Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Park Brake Type Independent, Mechanical Disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

Payload Capacity 1,200 lb

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Double wishbone/8.6 in Front Suspension /

Wheel Travel

Rear Suspension / **Wheel Travel**

Rear Tires

Double wishbone/9.1 in

Front Tires 25x10.00-12, radial

25x10.00-12, radial Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in **Overall Height** 75.8 in **Curb Weight** 1,594.2 lb*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Alloy

Additional Features Roof, Cast Aluminum Wheels

Color Choices Super Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471