

2023

TERYX KRX[®] 1000 eS

Kawasaki

Let the Good Times Roll[®]



MSRP

\$22,699



ICE GRAY/METALLIC ONYX BLACK



POWER		DETAILS	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Displacement	999cc	Cargo Bed Load Capacity	351 lb
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Payload Capacity	781 lb
Bore x Stroke	92.0 x 75.1mm	Seating Capacity	2
Compression Ratio	11.5:1	Towing Capacity	N/A
Fuel System	DFI [®] with two 50mm throttle bodies	Lighting	(2) LED headlights, (2) LED taillights, LED spotlight
Ignition	TCBI with Electronic Advance	Standard Ground Clearance/Maximum Ground Clearance†	14.0 in (std) / 14.4 in (max)
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft		
Engine Braking	Yes		
CAPABILITY			
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Frame	Ladder type, tubular steel
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in	Overall Length	132.1 in
Front Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR	Overall Width	68.1 in
Rear Tires	Maxxis [®] Carnivore 31 x 10.00R15 8PR	Overall Height	77.0 in
Steering	Electric Power Steering (EPS) / rack-and-pinion	Curb Weight	1,944.8 lb* / 1,947.0 lb* CA Model
Front Brakes	Dual hydraulic discs with two-piston calipers	Wheelbase	98.8 in
Rear Brakes	Dual hydraulic discs with single-piston calipers	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Ground Clearance	14.4 in (max), 14.0 in (std)	Wheel Type	Alloy with bead-lock wheels
Fuel Capacity	10.6 gal	Additional Features	Roof, Front Bumper
Turning Radius	20.3 ft	Color Choices	Ice Gray/Metallic Onyx Black

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**When linked to a smartphone via Bluetooth, notification of call and messages received will be indicated on the instrument display. Note, compatibility is limited to iOS type smartphones.

†Maximum ground clearance is measured at maximum pre-load suspension setting.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx[®] side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.