VERSYS® 650 LT





MSRP \$10,099



METALLIC SPARK BLACK/METALLIC FLAT SPARK BLACK



POWER

Engine 4-stroke, 2-cylinder, DOHC, 8 valves, liquid-

cooled

Displacement 649cc

Bore x Stroke 83.0 x 60.0mm

Compression

Ratio

10.8:1

Maximum Torque 47.0 lb-ft

Fuel System DFI® with 38mm Keihin throttle bodies (2)

Ignition TCBI with Electronic Advance

Transmission 6-speed with positive neutral finder

Final Drive Sealed chain

Electronic Rider Anti-lock Brake System (ABS), Kawasaki TRaction

Aids

Control (KTRC), Economical Riding Indicator

PERFORMANCE

Front Suspension 41mm telescopic fork with stepless adjustable / Wheel Travel rebound and spring preload/5.9 in

Rear Suspension / Wheel Travel

Single offset laydown shock with remote adjustable spring preload/5.7 in

Front Tire

120/70 ZR-17

Rear Tire 160/60 ZR-17

Front Brakes Dual 300mm petal-style discs with 2-piston

calipers, ABS

Rear Brakes Single 250mm petal-style disc with single-piston

caliper, ABS

DETAILS

Frame Type Double pipe diamond frame constructed from

high-tensile steel

25°/4.3 in Rake/Trail

Overall Length 85.2 in

Overall Width 33.1 in

Overall Height 53.5 in/55.9 in (windshield down/up)

Ground 6.7 in

Clearance

Seat Height 33.3 in

Curb Weight 482.9 lb* (+ approx. 20 lb* w/ saddlebags & hand

guards)

Fuel Capacity 5.5 gal

Wheelbase 55.7 in

Special Features TFT color instrumentation with Smartphone

> Connectivity via RIDEOLOGY THE APP, Cleanmount hard saddlebag system, featuring KQR™

mounts

Color Choices Metallic Spark Black/Metallic Flat Spark Black



