2024 ELIMINATOR®

Scan with camera

to view videos,

key features

and more.

Ōĩ







POWER		Front Brakes	Single 310mm disc with twin-piston caliper (and ABS)
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Rear Brakes	Single 220mm disc with single-piston caliper (and ABS)
Displacement	451cc		
Bore x Stroke	70.0 x 58.6mm	DETAILS	
Compression Ratio	11.3:1	Frame Type	Trellis, high-tensile steel
Maximum	31.7 lb-ft	Rake/Trail	30°/4.8 in
Torque	31.7 10-11	Overall Length	88.6 in
Fuel System	DFI 32mm Throttle Bodies	Overall Width	30.9 in
Ignition	TCBI w/ Digital Advance	Overall Height	43.3 in
Transmission	6-speed, return shift	Ground	5.9 in
Final Drive	Sealed chain	Clearance	
		Seat Height	28.9 in
PERFORMANCE		Estimated Dry Weight	361.6 lb** (ABS), 359.4 lb** (non-ABS)
Front Suspension /	41mm telescopic fork/4.7 in	Curb Weight	388.1 lb* (ABS), 385.9 lb* (non-ABS)
Wheel Travel		Fuel Capacity	3.4 gal
Rear Suspension /	Twin shocks/3.1 in	Wheelbase	59.8 in
Wheel Travel Front Tire	130/70-18	Special Features	Smartphone connectivity, RIDEOLOGY THE APP
Rear Tire	150/80-16	Color Choices	Pearl Storm Gray, Pearl Robotic White

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.