2024 KLX®110R







POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	112cc
Bore x Stroke	53.0 x 50.6mm
Compression Ratio	9.5:1
Fuel System	18mm Keihin carburetor and screw type throttle limiter on grip housing
Ignition	DC-CDI
Transmission	4-speed, return shift, automatic centrifugal and wet, multi-disc clutch
Final Drive	Chain

Front Tire 2.50 x 14 **Rear Tire** 3.00 x 12 **Front Brakes** 90mm mechanical drum, cable actuated **Rear Brakes** 110mm mechanical drum, rod actuated

DETAILS

18mm Keihin carburetor and screw type	Frame Type	Backbone frame, high-tensile steel
throttle limiter on grip housing	Rake/Trail	24.8°/2.0 in
DC-CDI	Overall Length	61.4 in
4-speed, return shift, automatic centrifugal and wet, multi-disc clutch	Overall Width	25.6 in
Chain	Overall Height	37.6 in
	Ground	8.5 in
ANCE	Clearance	
	Seat Height	26.8 in
30mm hydraulic telescopic fork/4.3 in	Curb Weight	167.5 lb*
	Fuel Capacity	1.0 gal
Swingarm with single hydraulic shock/4.3 in	Wheelbase	42.3 in
	Color Choices	Lime Green, Battle Gray

PERFORMANCE

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Scan with camera

to view videos,

key features

and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.