

2024

KLX[®]230 S



MSRP NON-ABS

\$4,999

MSRP ABS

\$5,299

- LIME GREEN
- BATTLE GRAY



POWER		Rear Tire	4.10 x 18
Engine	4-stroke single, SOHC, air-cooled	Front Brakes	Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)
Bore x Stroke	67.0 x 66.0mm	DETAILS	
Compression Ratio	9.4:1	Frame Type	Perimeter, high-tensile steel
Maximum Torque	13.2 lb-ft @ 6,400 rpm	Rake/Trail	24.6° / 3.7 in
Fuel System	DFI [®] with 32mm throttle body	Overall Length	81.8 in
Ignition	TCBI with Electronic Advance	Overall Width	33.2 in
Transmission	6-speed	Overall Height	44.8 in
Final Drive	Sealed chain	Ground Clearance	9.4 in
Electronic Rider Aids	Anti-lock Brake System (ABS)	Seat Height	33.3 in
PERFORMANCE		Curb Weight	291.0/293.2 lb* 50-State Model
Front Suspension / Wheel Travel	37mm telescopic fork/7.8 in	Fuel Capacity	2.0 gal
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.7 in	Wheelbase	53.7 in
Front Tire	2.75 x 21	Special Features	ERGO-FIT [®] , LCD Instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE
		Color Choices	Lime Green, Battle Gray

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.