²⁰²⁴ KLX[®]230R







Rear Tire 100/100-18 **POWER Front Brakes** Single 240mm petal disc with a dualpiston caliper Engine 4-stroke single, SOHC, air-cooled Single 220mm petal disc with single-**Rear Brakes** Displacement 233cc piston caliper **Bore x Stroke** 67.0 x 66.0mm **DETAILS** Compression 9.4:1 Ratio High-tensile steel, box-section Frame Type **Fuel System** DFI® with 32mm Keihin throttle body perimeter Ignition **TCBI Electronic Advance** 26.5°/4.4 in Rake/Trail Transmission 6-speed, return shift with wet multi-disc **Overall Length** 80.5 in manual clutch **Overall Width** 33.1 in **Final Drive** Chain **Overall Height** 47.2 in PERFORMANCE 11.8 in Ground Clearance 37mm telescopic fork/9.8 in Front 36.4 in Seat Height Suspension / Wheel Travel 253.6 lb* / 262.3 lb* CA Model **Curb Weight** Uni-Trak[®] linkage system and single Rear **Fuel Capacity** 1.7 gal Suspension / shock with adjustable spring preload/9.9 in Wheel Travel Wheelbase 53.5 in

Front Tire

80/100-21

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Lime Green, Battle Gray

Color Choices