MULE PRO-FXR™ 1000 LE





\$16,199



ICE GRAY



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

DFI® with 38mm throttle body **Fuel System**

Transmission Continuously Variable Transmission (CVT) with (L,H,N,R)

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

90 amp

CAPABILITY

Double wishbone/11.0 in Front Suspension / **Wheel Travel**

Rear Suspension / Double wishbone/10.1 in Wheel Travel

Front Tires 27 x 9.00-12, radial

27 x 11.00-12, radial Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Independent, Mechanical Disc **Park Brake Type**

Ground Clearance 13.2 in (max), 12.2 in (std)

Fuel Capacity 7.9 gal **Turning Radius** 14.0 ft

Cargo Bed 37.6 x 53.3 x 11.0 in

Dimensions (LxWxH)

Cargo Bed Load 999 lb / 600.0 lb CA Model Capacity

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity

Towing Capacity 2.000 lb

(2) Halogen headlights. (2) LED headlights Lighting

DETAILS

Overall Length 122.0 in **Overall Width** 64.0 in **Overall Height** 78.5 in

Curb Weight 1,746.4 lb* / 1,748.6 lb* CA Model

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

Wheel Type Alloy

Additional Features Roof, Rear Bumper, Contoured Two-Tone Bench Seat,

Additional Cup Holders

Color Choices Ice Gray



Rear Tires

