

2024

MULE PRO-FXT™ 1000 LE



MSRP
\$18,799

- METALLIC SIERRA BLUE
- METALLIC ONYX BLACK



POWER		Ground Clearance	12.6 in (max), 11.6 in (std)
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	Fuel Capacity	7.9 gal
Displacement	999cc	Turning Radius	16.0 ft
Maximum Torque	61.5 lb-ft	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Load Capacity	999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model
Compression Ratio	10.1:1	Payload Capacity	1,616.3 lb / 1,263.5 lb CA Model
Fuel System	DFI® with 38mm throttle body	Seating Capacity	3-person (1 row), 6 person (2 row)
Transmission	Continuously Variable Transmission (CVT) with (L,H,N,R)	Towing Capacity	2,000 lb
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock	Lighting	(2) Halogen headlights. (2) LED headlights
Engine Braking	Yes	DETAILS	
Alternator Output (max)	90 amp	Overall Length	135.8 in
CAPABILITY		Overall Width	64.0 in
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Overall Height	80.9 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Curb Weight	1,913.9 lb* / 1,916.1 lb* CA Model
Front Tires	26 x 9.00-12, radial	Wheelbase	92.3 in
Rear Tires	26 x 11.00-12, radial	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Steering	Electric Power Steering (EPS), Tilt steering	Wheel Type	Alloy
Front Brakes	Dual Disc, 2 piston caliper	Additional Features	Roof, Additional Front Cup Holders
Rear Brakes	Dual Disc, 1 piston caliper	Color Choices	Metallic Onyx Black, Metallic Sierra Blue
Park Brake Type	Independent, Mechanical Disc		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.