## **MULE PRO-MX™ EPS**





**MSRP** \$14,099



FIRECRACKER RED



TIMBERLINE GREEN



## **POWER**

**Engine** 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement

42.7 lb-ft @ 5,000 rpm **Maximum Torque** 

102.0 x 85.0mm Bore x Stroke

**Compression Ratio** 10.3:1

**Fuel System** DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal Transmission

**Final Drive** Selectable 2WD/4WD, shaft Dual mode rear differential with

differential lock

**Engine Braking** 

**Alternator Output** 35.7 amp

(max)

**Ground Clearance** 10.6 in

**Fuel Capacity** 9.5 gal

**Turning Radius** 14.0 ft

Cargo Bed **Dimensions (LxWxH)** 

33.4 x 44.1 x 9.1 in

**Cargo Bed Load** 

Capacity

699 lb / 600 lb CA Model

**Payload Capacity** 1,200 lb

**Seating Capacity** 

**Towing Capacity** 1,500 lb

Lighting (2) Halogen headlights. (2) LED headlights

## CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Wheel Travel

**Rear Tires** 

Double wishbone/9.1 in

**Front Tires** 25 x 8.00-12, radial

25 x 10.00-12, radial Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

**Park Brake Type** 

Independent, Mechanical Disc

## **DETAILS**

**Overall Length** 110.0 in **Overall Width** 60.0 in **Overall Height** 74.4 in

**Curb Weight** 1,587.6 lb\* / 1,589.8 lb\* CA Model

Wheelbase 78.9 in

Multi-function display includes digital speedometer, fuel Instruments gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Steel

**Color Choices** Timberline Green, Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

**Kawasaki Protection** 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.