NINJA® 500 SE ABS





\$6.399



PASSION RED/METALLIC FLAT SPARK BLACK/ METALLIC MATTE DARK GRAY



POWER

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke 70.0 x 58.6mm

Compression Ratio 11.3:1

Maximum

51.0 hp1 @ 10,000 rpm Horsepower

31.7 lb-ft @ 7,500 rpm **Maximum Torque**

Fuel System DFI® with dual 32mm throttle bodies

Ignition TCBI with Digital Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider Economical Riding Indicator, Anti-lock Brake System

Aids

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm hydraulic telescopic fork/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with adjustable spring

preload/5.1 in

Front Tire 110/70-17 **Rear Tire** 150/60-17

Front Brakes Single 310mm semi-floating disc with 2-piston

calipers and ABS

Rear Brakes Single 220mm disc with single-piston caliper and ABS

DETAILS

Frame Type Trellis, high-tensile steel

24.7°/3.6 in Rake/Trail

Overall Length 78.5 in

Overall Width 28.7 in

Overall Height 46.5 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Estimated Dry

Weight

348.4 lb** / 350.6 lb** 50-State Model

Curb Weight 379.3 lb* / 381.5 lb* 50-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features

ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP,

Kawasaki's Intelligent Proximity Activation Start

System (KIPASS), USB-C outlet

Color Choices Passion Red/Metallic Flat Spark Black/Metallic Matte

Dark Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.