# 2024 NINJA<sup>®</sup> ZX<sup>™</sup>-4R ABS







### **POWER**

Engine	4-stroke, In-Line Four, OHC, 16-valve, liquid- cooled	
Displacement	399cc	
Bore x Stroke	57.0 x 39.1mm	
Compression Ratio	12.3:1	
Fuel System	DFI® with 34mm throttle valves (4)	
Ignition	Digital	
Transmission	6-speed, manual, return shift	
Final Drive	Chain	
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC) (3-mode), Power Modes, Anti-lock Brake System (ABS)	

#### **Front Tire** 110/70-17 **Rear Tire** 160/60-17 **Front Brakes** Dual 290mm discs, ABS **Rear Brakes** Single 220mm disc, ABS

### **DETAILS**

	Frame Type	Trellis, high-tensile steel
	Rake/Trail	23.5°/3.8 in
	Overall Length	78.3 in
	Overall Width	30.1 in
	Overall Height	43.7 in
	Ground Clearance	5.3 in
	Seat Height	31.5 in
	Curb Weight	414.5 lb*
ı.7	Fuel Capacity	4.0 gal
	Wheelbase	54.3 in
	Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP
	Color Choices	Metallic Spark Black

## PERFORMANCE

Front 37mm inverted fork with SFF-BP internals/4. Suspension / in Wheel Travel Rear

Horizontal Back-link, Showa shock w/ adjustable spring preload/4.4 in

Scan with camera to view videos, key features and more.

Suspension /

Wheel Travel



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.