2024 **RIDGE[®] HVAC**







12.9 gal

15.0 ft

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,499/1,100 lb CA Model

Ladder type, tubular steel

1,938.2/1,940.5 lb** CA Model

3, bench seat

All-LED lighting

2,500 lbs

124.4 in

64.0 in

81.3 in

12.6/13.6 in (max preload); 12.6 in CA Model

POWER

Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	92.0 hp ¹ @ 8,500 rpm
Maximum Torque	65.8 lb-ft @ 5,500 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

CAPABILITY

CAPABILITY		Curb Weight	2,044.0/2,046.2 lb* CA Model
Front Suspension /	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in
Wheel Travel Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical
Front Tires	Duro 27 x 9-14		Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking
Rear Tires	Duro 27 x 11-14		indicator, oil pressure, water temperature)
Wheel Type	14" Aluminum	Additional Features	Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full- color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Candy Persimmon Red

Ground Clearance

Fuel Capacity

Turning Radius

(LxWxH) **Cargo Bed Load**

Capacity **Payload Capacity**

Lighting

Frame

Seating Capacity

Towing Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Estimated Dry Weight

Cargo Bed Dimensions



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.