

2024

TERYX® KRX4™ 1000 SE eS



MSRP
\$27,699

 METALLIC FLAT RAW GRAYSTONE



POWER		Fuel Capacity	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Turning Radius	10.6 gal
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	23.3 ft
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Cargo Bed Load Capacity	14.6 x 33.1 x 9.1 in
Bore x Stroke	92.0 x 75.1mm	Payload Capacity	351 lb
Compression Ratio	11.5:1	Seating Capacity	1,001 lb
Fuel System	DFI® with two 50mm throttle bodies	Towing Capacity	4
Ignition	TCBI with Electronic Advance	Lighting	N/A
Starting System	Electric		(2) LED headlights, (2) LED taillights, LED stoplight
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	DETAILS	
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	157.3 in
CAPABILITY		Overall Width	68.1 in
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Overall Height	79.3 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in	Curb Weight	2,207.2 lb* / 2,209.4 lb* CA Model
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Wheelbase	125.8 in
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Steering	Electric Power Steering (EPS) / rack-and-pinion	Wheel Type	Alloy wheels
Front Brakes	Dual hydraulic discs with two-piston calipers	Additional Features	Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45 Winch
Rear Brakes	Dual hydraulic discs with single-piston calipers	Color Choices	Metallic Flat Raw Graystone
Ground Clearance	14.4 in (max), 13.6 in (std)		



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.