

2024

TERYX® KRX4™ 1000 SE



MSRP

\$25,199

 PEARL MATTE SAGE GREEN/METALLIC CARBON GRAY



| POWER                           |                                                                                                                                                                             | Turning Radius               | 23.3 ft                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled                                                                                                                        | Cargo Bed Dimensions (LxWxH) | 14.6 x 33.1 x 9.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Displacement                    | 999cc                                                                                                                                                                       | Cargo Bed Load Capacity      | 351 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Maximum Torque                  | 76.7 lb-ft @ 7,000 rpm                                                                                                                                                      | Payload Capacity             | 1,001 lb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Bore x Stroke                   | 92.0 x 75.1mm                                                                                                                                                               | Seating Capacity             | 4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Compression Ratio               | 11.5:1                                                                                                                                                                      | Towing Capacity              | N/A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Fuel System                     | DFI® with two 50mm throttle bodies                                                                                                                                          | Lighting                     | (2) LED headlights, (2) LED taillights, LED stoilight                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Ignition                        | TCBI with Electronic Advance                                                                                                                                                | DETAILS                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Starting System                 | Electric                                                                                                                                                                    | Frame                        | Ladder type, tubular steel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Transmission                    | Automatic CVT with centrifugal clutch (H,L,N,R)                                                                                                                             | Overall Length               | 157.3 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Final Drive                     | Selectable 2WD/4WD with locking front differential, shaft                                                                                                                   | Overall Width                | 68.1 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Engine Braking                  | Yes                                                                                                                                                                         | Overall Height               | 79.3 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| CAPABILITY                      |                                                                                                                                                                             | Curb Weight                  | 2,163.1 lb* / 2,165.3 lb* CA Model                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Front Suspension / Wheel Travel | Double wishbone, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/18.6 in                     | Wheelbase                    | 125.8 in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Rear Suspension / Wheel Travel  | 4-link trailing-arm rear suspension, FOX 2.5 LSC Piggyback Shocks, dual-rate coil-over springs, fully adjustable preload, and 24-way adjustable compression damping/21.1 in | Instruments                  | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp. |
| Front Tires                     | Maxxis® Carnivore 31 x 10.00R15 8PR                                                                                                                                         | Wheel Type                   | Alloy wheels                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Rear Tires                      | Maxxis® Carnivore 31 x 10.00R15 8PR                                                                                                                                         | Additional Features          | Roof, WARN® VRX 45 Winch                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Steering                        | Electric Power Steering (EPS) / rack-and-pinion                                                                                                                             | Color Choices                | Pearl Matte Sage Green/Metallic Carbon Gray                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Front Brakes                    | Dual hydraulic discs with two-piston calipers                                                                                                                               |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Rear Brakes                     | Dual hydraulic discs with single-piston calipers                                                                                                                            |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Ground Clearance                | 14.4 in (max), 13.6 in (std)                                                                                                                                                |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Fuel Capacity                   | 10.6 gal                                                                                                                                                                    |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.