TERYX® S LE





\$15,499



METALLIC MATTE TWILIGHT BLUE/SUPER BLACK



ICE GRAY/SUPER BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DFI® with two 36mm Mikuni throttle bodies **Fuel System**

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive**

Engine Braking

Ground Clearance 12.2 in (max) / 11.2 in (std)

Fuel Capacity 7.9 gal

Turning Radius 17.7 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

600 lb

Payload Capacity 1,100 lb

Seating Capacity

Towing Capacity 1,300 lb

(4) LED headlights, (2) incandescent taillights, Lighting

27.6 x 43.3 x 10.4 in

incandescent stoplight

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Electric Power Steering (EPS) / rack-and-pinion **Steering**

Front Brakes Dual hydraulic discs with two-piston calipers

Sealed, oil-bathed, multi-disc Rear Brakes

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 118.1 in **Overall Width** 62.2 in

Overall Height 78.5 in

Curb Weight 1,596.4 lb* / 1,598.6 lb* CA Model

Wheelbase 88.2 in

Multi-function digital meter with speedometer, fuel gauge, Instruments

clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Alloy **Wheel Type**

Additional Features Roof

Color Choices Metallic Matte Twilight Blue-/Super Black, Ice Gray/Super



