

2024

VULCAN® S

Kawasaki
Let the Good Times Roll®



MSRP NON-ABS
\$7,349

MSRP ABS
\$7,899



PEARL SAND KHAKI/EBONY



METALLIC FLAT SPARK BLACK



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Torque	46.3 lb-ft @ 6,600 rpm
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)

Front Tire	120/70x18
Rear Tire	160/60x17
Front Brakes	Single 300mm disc with twin-piston caliper, (and ABS)
Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in

DETAILS

Frame Type	High-tensile steel diamond frame
Rake/Trail	31° / 4.7 in
Overall Length	90.9 in
Overall Width	34.6 in
Overall Height	43.3 in
Ground Clearance	5.1 in
Seat Height	27.8 in
Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
Fuel Capacity	3.7 gal
Wheelbase	62.0 in
Color Choices	Pearl Sand Khaki/Ebony, Metallic Flat Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.