2024 **Z650RS ABS**







Rear Suspension Horizontal back-link with adjustable preload, POWER / Wheel Travel swingarm/5.1 in **Front Tire** 120/70 ZR17 Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled **Rear Tire** 160/60 ZR17 Displacement 649cc Dual 300mm petal-style discs with two-piston **Front Brakes** Bore x Stroke 83.0 x 60.0mm calipers, (and ABS) Compression 10.8:1 **Rear Brakes** Single 220mm petal-style disc, (and ABS) Ratio Maximum 48.5 lb-ft @ 6,700 rpm DETAILS Torque DFI® with Keihin 36mm throttle bodies **Fuel System Frame Type** Trellis, high tensile steel TCBI with Electronic Advance Ignition 24.0°/3.9 in Rake/Trail Transmission 6-speed, return shift **Overall Length** 81.3 in **Final Drive** Sealed chain 31.5 in **Overall Width**

Electronic Rider Economical Riding Indicator, Kawasaki TRaction Control (KTRC - 3 Modes), Anti-lock Aids Brake System (ABS)

PERFORMANCE

Front Suspension / Wheel Travel Telescopic fork/4.9 in

Overall Height 43.9 in 4.9 in Ground Clearance **Seat Height** 31.5 in **Curb Weight** 412.3 lb* **Fuel Capacity** 3.2 gal Wheelbase 55.3 in **Color Choices** Ebony/Metallic Matte Carbon Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.