BRUTE FORCE® 750





MSRP **\$9,999**



TIMBERLINE GREEN



POWER

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 749c

Bore x Stroke 85.0 x 66.0mm

Compression Ratio 9.3:1

Maximum Torque 42.7 lb-ft @ 4,750 rpm

Fuel System DFI® with two 34mm throttle bodies

Ignition Digital DC-CDI

Transmission Automatic Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

DETAILS

Dry Weight

Steering

Rear

Lighting

Turning Radius

Towing Capacity

Total Rack Capacity

Rack Capacity, Front/

Frame Type Double-cradle, high-tensile tubular steel

All-LED lighting

Rack-and-pinion

10.5 ft

1,250 lb

264.5 lb

88.0/176.0 lb

Tread Width 37.0/35.6 in

Overall Length 86.0 in

Overall Width 46.1 in

Overall Height 47.6 in

Seat Height 35.2 in

Curb Weight 707.8 lb*

Wheelbase 50.6 in

Instruments

Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock

(12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, and battery

voltage)

661.5 lb**

Special Features Full-color TFT Instrumentation w/ Smartphone Connectivity

via RIDEOLOGY THE APP POWERSPORTS, KQR™ system

Color Choices Timberline Green

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, adjustable spring preload/6.9 in

Rear Suspension / Wheel Travel Double wishbone, adjustable spring preload/7.4 in

Front Tire

AT 25 x 8-12

Rear Tire AT 25 x 10-12

Front Brakes Dual hydraulic 176mm discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc with independent park brake

Ground Clearance 9.0 in/9.7 in (max preload)

Starting System Electric

Fuel Capacity 5.0 gal

Scan with camera to view videos, key features and more.



