# **BRUTE FORCE® 750 LE EPS**





### MSRP **\$11,999**



PEARL MATTE SAGE GREEN



Steering

Rear

Lighting

**Turning Radius** 

**Towing Capacity** 

**Total Rack Capacity** 

Rack Capacity, Front/

CYPHER CAMO GRAY



Rack-and-pinion w/ Electric Power Steering (EPS)

#### **POWER**

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 7490

Bore x Stroke 85.0 x 66.0mm

Compression Ratio 9.3:1

Maximum Torque 42.8 lb-ft @ 4,750 rpm

Fuel System DFI® with two 34mm throttle bodies

Ignition Digital DC-CDI

Transmission Automatic Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

# DETAILS

Frame Type Double-cradle, high-tensile tubular steel

47.6 in

10.5 ft

1,250 lb

264.5 lb

88.0/176.0 lb

All-LED lighting

Tread Width 37.0/35.6 in

Overall Length 86.0 in

Overall Width 46.1 in

Seat Height 35.2 in

**Overall Height** 

Estimated Dry Weight 685.8 lb\*\*

Curb Weight 732.1 lb\*

Wheelbase 50.6 in

Instruments

Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock

(12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and

battery voltage)

Special Features Full-color TFT Instrumentation w/ Smartphone Connectivity

via RIDEOLOGY THE APP POWERSPORTS, KQR™ system

**Color Choices** Pearl Matte Sage Green, Cypher Camo Gray

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone, adjustable spring preload/6.9 in

Rear Suspension / Wheel Travel Double wishbone, adjustable spring preload/7.4 in

Front Tire

AT 25 x 8-12

Rear Tire AT 25 x 10-12

Front Brakes Dual hydraulic 176mm discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc with independent park brake

**Ground Clearance** 9.0 in/9.7 in (max preload)

Starting System Electric
Fuel Capacity 5.0 gal

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. © 2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.