2025 ELIMINATOR®







POWER		Front Brakes	Single 310mm disc with twin-piston caliper (and ABS)
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Rear Brakes	Single 220mm disc with single-piston caliper (and ABS)
Displacement	451cc		
Bore x Stroke	70.0 x 58.6mm	DETAILS	
Compression Ratio	11.3:1	Frame Type	Trellis, high-tensile steel
Maximum Torque	31.7 lb-ft @ 7,500 rpm	Rake/Trail	30.0°/4.8 in
Fuel System	DFI® with 32mm throttle bodies	Overall Length	88.6 in
Ignition	TCBI w/ Digital Advance	Overall Width	30.9 in
Transmission	6-speed, return shift	Overall Height	43.3 in
Final Drive	Sealed chain	Ground Clearance	5.9 in
Electronic Rider Aids	Anti-lock Brake System (ABS only)	Seat Height	28.9 in
DEDEODMANCE		Estimated Dry Weight	361.6 lb** (ABS) / 359.4 lb** (non-ABS)
PERFORMANCE		-	388.1 lb* (ABS) / 385.9 lb* (non-ABS)
Front	41mm telescopic fork/4.7 in	Curb Weight	388.1 ID" (ABS) / 385.9 ID" (NOII-ABS)
Suspension /		Fuel Capacity	3.4 gal
Wheel Travel		Wheelbase	59.8 in
Rear Suspension / Wheel Travel	Twin shocks/3.1 in	Special Features	ERGO-FIT [®] , Smartphone Connectivity via RIDEOLOGY THE APP
Front Tire	130/70-18	Color Choices	Metallic Flat Spark Black, Pearl Sand Khaki
Rear Tire	150/80-16		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.