ELIMINATOR®





MSRP NON-ABS **\$6.499**

MSRP ABS **\$6,799**



METALLIC FLAT SPARK BLACK



PEARL SAND KHAKI



D	n	V	M		D
Г	u	N.	N	Е	π

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke 70.0 x 58.6mm

Compression

Ratio

11.3:1

Maximum Torque 31.7 lb-ft @ 7,500 rpm

Fuel System

DFI® with 32mm throttle bodies

Ignition

TCBI w/ Digital Advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Anti-lock Brake System (ABS only)

PERFORMANCE

Front
Suspension /
Wheel Travel

41mm telescopic fork/4.7 in

Rear Suspension / Wheel Travel

Twin shocks/3.1 in

Front Tire

130/70-18

Rear Tire 150/80-16

Front Brakes

Single 310mm disc with twin-piston caliper

(and ABS)

Rear Brakes

Single 220mm disc with single-piston caliper

(and ABS)

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 30.0°/4.8 in

Overall Length 88.6 in

Overall Width 30.9 in

Overall Height 43.3 in

Ground 5.9 in

Clearance

Seat Height 28.9 in

Dry Weight 361.6 lb** (ABS) / 359.4 lb** (non-ABS)

Curb Weight 388.1 lb* (ABS) / 385.9 lb* (non-ABS)

Fuel Capacity 3.4 gal

Wheelbase 59.8 in

Special Features ERGO-FIT®, Smartphone Connectivity via

RIDEOLOGY THE APP

Color Choices Metallic Flat Spark Black, Pearl Sand Khaki





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki.com for full product details.