KLX[®]230 S





MSRP NON-ABS \$4,999

MSRP ABS \$5,299



LIME GREEN



POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Torque 13.0 lb-ft @ 6,400 rpm

Fuel System DFI® with 32mm throttle body

Ignition TCBI with Electronic Advance

Transmission

Final Drive

Electronic Rider

Aids

6-speed

Sealed chain

Anti-lock Brake System (ABS)

PERFORMANCE

37mm telescopic fork/7.9 in Front Suspension / **Wheel Travel Rear Suspension** Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in / Wheel Travel **Front Tire** 2.75 x 21

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

Single 220mm petal disc with single-piston **Rear Brakes**

caliper (and ABS)

DETAILS

Clearance

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.6°/3.8 in

Overall Length 81.9 in

Overall Width 33.3 in

Overall Height 44.9 in

Ground 9.4 in

Seat Height 33.3 in

Dry Weight 275.6 lb** (ABS), 273.4 lb** (non-ABS) / 277.7 lb**

(ABS), 275.5 lb** (non-ABS) 50-State Model

291.1 lb* (ABS), 288.9 lb* (non-ABS) / 293.3 lb* **Curb Weight**

(ABS), 291.1 lb* (non-ABS) 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with

Smartphone Connectivity via RIDEOLOGY THE

APP MOTORCYCLE

Color Choices Lime Green



Rear Tire



4.10 x 18