2025 KLX®300R







POWER 4-stroke, single-cylinder, DOHC, liquid-Engine cooled Displacement 292cc **Bore x Stroke** 78.0 x 61.2mm Compression 11.0:1 Ratio DFI® with 34mm Keihin throttle body **Fuel System** Ignition TCBI with electronic advance Transmission 6-speed, return shift with wet multi-dis manual clutch **Final Drive** Chain

PERFORMANCE

43mm inverted telescopic fork with Front adjustable compression damping/11.2 Suspension / Wheel Travel Uni-Trak[®] gas charged shock with Rear piggyback reservoir with adjustable Suspension / compression, rebound damping and Wheel Travel spring preload/11.2 in

Front Tire	3.0 x 21
Rear Tire	4.6 x 18
Front Brakes	Single 270mm petal disc with a dual- piston caliper
Rear Brakes	Single 240mm petal disc with single- piston caliper

DETAILS

	Frame Type	Semi-double cradle
	Rake/Trail	26.9°/4.3 in
isc	Overall Length	86.6 in
	Overall Width	32.5 in
	Overall Height	49.0 in
	Ground Clearance	11.8 in
! in	Seat Height	35.4 in
	Curb Weight	282.2 lb* / 286.7 lb* 50-State Model
	Fuel Capacity	2.1 gal
	Wheelbase	56.5 in
	Color Choices	Lime Green, Battle Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.