

2025  
KX™112



MSRP  
\$5,649

 LIME GREEN



POWER

Engine	2-stroke, single-cylinder with exhaust power valve (KIPS), liquid-cooled
Displacement	112cc
Bore x Stroke	52.5 x 51.6mm
Compression Ratio	9.9:1 (low speed) / 8.6:1 (high speed)
Fuel System	28mm Keihin carburetor
Ignition	CDI with digital advance
Transmission	6-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	90/100-16
Front Brakes	Single 220mm petal disc with dual-piston caliper
Rear Brakes	Single 184mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel perimeter design with subframe member
Rake/Trail	29.0° / 4.3 in
Overall Length	75.6 in
Overall Width	30.1 in
Overall Height	45.3 in
Ground Clearance	13.0 in
Seat Height	34.3 in
Curb Weight	169.7 lb*
Fuel Capacity	1.32 gal
Wheelbase	51.6 in
Special Features	ERGO-FIT®
Color Choices	Lime Green

PERFORMANCE

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in
Front Tire	70/100-19

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.