## 2025 MULE<sup>™</sup> 4010 TRANS4x4®





## POWER

Engine	4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled
Displacement	617cc
Maximum Torque	34.7 lb-ft @ 2,500 rpm
Bore x Stroke	76.0 x 68.0mm
<b>Compression Ratio</b>	10:3:1
Fuel System	DFI® with 34mm Mikuni throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	No
Alternator Output (max)	23 amp

Park Brake Type	Independent, mechanical drum		
Ground Clearance	7.1 in		
Fuel Capacity	6.3 gal		
Turning Radius	12.8 ft		
Cargo Bed Dimensions (LxWxH)	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4- person)		
Cargo Bed Load Capacity	800 lb (2-person) / 401 lb (4-person)		
Payload Capacity	1,330 lb		
Seating Capacity	2-4		
Towing Capacity	1,200 lb		
Lighting	(2) Halogen headlights, (2) tail/brake lights		

## DETAILS

	Overall Length	128.5 in
n Strut/3.9 in	Overall Width	58.5 in
	Overall Height	75.8 in
e/2.8 in	Estimated Dry Weight	1,521.5 lb**
	Curb Weight	1,587.6 lb*
	Wheelbase	85.2 in
pinion w/ Electric Power Steering (EPS)	Instruments	Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter
	Color Choices	Timberline Green, Dark Royal Red

Scan with camera to view videos, key features and more.

**CAPABILITY** 

Front Suspension /

**Rear Suspension /** 

Wheel Travel

Wheel Travel Front Tires

**Rear Tires** 

Steering

**Front Brakes** 

**Rear Brakes** 



MacPhersor

**DeDion Axle** 

23 x 11-10

23 x 11-10

Rack-and-p

Drum

Drum

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

