

2025

MULE™ 4010 TRANS4x4®

Kawasaki

Let the Good Times Roll®



MSRP

\$13,549

TIMBERLINE GREEN

DARK ROYAL RED



| POWER                           |                                                                               | Park Brake Type              | Independent, mechanical drum                                                                          |
|---------------------------------|-------------------------------------------------------------------------------|------------------------------|-------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled                          | Ground Clearance             | 7.1 in                                                                                                |
| Displacement                    | 617cc                                                                         | Fuel Capacity                | 6.3 gal                                                                                               |
| Maximum Torque                  | 34.7 lb-ft @ 2,500 rpm                                                        | Turning Radius               | 12.8 ft                                                                                               |
| Bore x Stroke                   | 76.0 x 68.0mm                                                                 | Cargo Bed Dimensions (LxWxH) | 50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person)                                   |
| Compression Ratio               | 10:3:1                                                                        | Cargo Bed Load Capacity      | 800 lb (2-person) / 401 lb (4-person)                                                                 |
| Fuel System                     | DFI® with 34mm Mikuni throttle body                                           | Payload Capacity             | 1,330 lb                                                                                              |
| Transmission                    | Continuously Variable Transmission (CVT) with (H,L,N,R)                       | Seating Capacity             | 2-4                                                                                                   |
| Final Drive                     | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Towing Capacity              | 1,200 lb                                                                                              |
| Engine Braking                  | No                                                                            | Lighting                     | (2) Halogen headlights, (2) tail/brake lights                                                         |
| Alternator Output (max)         | 23 amp                                                                        | DETAILS                      |                                                                                                       |
| CAPABILITY                      |                                                                               | Overall Length               | 128.5 in                                                                                              |
| Front Suspension / Wheel Travel | MacPherson Strut/3.9 in                                                       | Overall Width                | 58.5 in                                                                                               |
| Rear Suspension / Wheel Travel  | DeDion Axle/2.8 in                                                            | Overall Height               | 75.8 in                                                                                               |
| Front Tires                     | 23 x 11-10                                                                    | Estimated Dry Weight         | 1,521.5 lb**                                                                                          |
| Rear Tires                      | 23 x 11-10                                                                    | Curb Weight                  | 1,587.6 lb*                                                                                           |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS)                              | Wheelbase                    | 85.2 in                                                                                               |
| Front Brakes                    | Drum                                                                          | Instruments                  | Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter |
| Rear Brakes                     | Drum                                                                          | Color Choices                | Timberline Green, Dark Royal Red                                                                      |

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.