MULE PRO-DX™ EPS





\$17,999



BRIGHT WHITE



54.1 x 53.7 x 11.0 in

999 lb

POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 55 amp

(max)

Ground Clearance 10.4 in **Fuel Capacity** 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load Capacity

Payload Capacity 1,574 lb

Seating Capacity 3-person

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Wheel Travel

Double wishbone/8.7 in Front Suspension / **Wheel Travel**

Double wishbone/8.5 in (L)/8.7 in (R) **Rear Suspension /**

26 x 9-12 **Front Tires Rear Tires** 26 x 11-12

Steering Electric Power Steering (EPS), Tilt steering

Dual disc, 2-piston caliper **Front Brakes Rear Brakes** Dual disc, 1-piston caliper **Park Brake Type**

Independent, mechanical disc

DETAILS

Overall Length 133.3 in **Overall Width** 64.0 in

Overall Height 77.4 in

Estimated Dry 1,781.6 lb** Weight

Curb Weight 1,858.8 lb*

Wheelbase 92.3 in

Multi-function display includes digital speedometer, fuel Instruments

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Color Choices Bright White

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied) All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.