MULE PRO-DXT™ EPS





\$19,799



SUPER BLACK



POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 74.0 x 77.0mm

Compression Ratio 23.5:1

Fuel System Bosch in-line injection pump

Transmission

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Alternator Output 55 amp

(max)

Continuously Variable Transmission (CVT) with (H,L,N,R)

Engine Braking

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26 x 9-12

Rear Tires 26 x 11-12

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual disc, 2-piston caliper **Rear Brakes** Dual disc, 1-piston caliper

Independent, mechanical disc **Park Brake Type**

Ground Clearance

Turning Radius

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Fuel Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

10.2 in

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

person)

1,574 lb

3-person (1-row), 6-person (2-row)

999 lb (3-person) / 350 lb (6-person)

2,000 lb

(2) Halogen headlights

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Curb Weight 1,942.6 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

Super Black

Color Choices

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471