## **MULE PRO-DXT™ FE EPS**





\$19,999



**BRIGHT WHITE** 



## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Maximum Torque** 38.3 lb-ft @ 2,400 rpm

**Bore x Stroke** 74.0 x 77.0mm

**Compression Ratio** 23.5:1

**Fuel System** Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 55 amp

(max)

**Ground Clearance Fuel Capacity** 

**Turning Radius** 16.0 ft

**Cargo Bed** 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

**Dimensions (LxWxH)** person)

**Cargo Bed Load** 

Capacity

999 lb (3-person) / 350 lb (6-person)

10.2 in

7.9 gal

**Payload Capacity** 1,574 lb

**Seating Capacity** 3-person (1-row), 6-person (2-row)

**Towing Capacity** 2,000 lb

Lighting (2) Halogen headlights

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel** 

Double wishbone/8.5 in (L)/8.7 in (R)

**Front Tires** 26 x 9-12 **Rear Tires** 26 x 11-12

Electric Power Steering (EPS), Tilt steering Steering

Dual disc, 1-piston caliper

**Front Brakes** Dual disc, 2-piston caliper

Independent, mechanical disc **Park Brake Type** 

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 79.5 in

**Curb Weight** 1,971.3 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

**Additional Features** Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

**Color Choices Bright White** 

Scan with camera to view videos, key features and more.

**Rear Brakes** 



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471