

2025

MULE PRO-FX™ 1000 HD EDITION

Kawasaki

Let the Good Times Roll®



MSRP

\$16,799

FIRECRACKER RED



POWER		Ground Clearance	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	Fuel Capacity	11.9 in (max), 11.8 in (std)
Displacement	999cc	Turning Radius	7.9 gal
Maximum Torque	61.5 lb-ft @ 4,500 rpm	Cargo Bed Dimensions (LxWxH)	16.0 ft
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Load Capacity	54.1 x 53.3 x 11.0 in
Compression Ratio	10.1:1	Payload Capacity	999/600 lb CA Model
Fuel System	DFI® with 38mm throttle body	Seating Capacity	1,616.3/1,263.5 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Towing Capacity	3
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Lighting	2,000 lb
Engine Braking	Yes	DETAILS	
Alternator Output (max)	90 amp		
CAPABILITY		Overall Length	136.6 in
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Overall Width	64.0 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Overall Height	81.1 in
Front Tires	26 x 9-12, radial	Estimated Dry Weight	1,816.9/1,819.1 lb** CA Model
Rear Tires	26 x 11-12, radial	Curb Weight	1,891.9/1,894.1 lb* CA Model
Wheel Type	Steel	Wheelbase	92.3 in
Steering	Rack-and-pinion	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual disc, 2-piston caliper	Additional Features	Roof, Rear Bumper, Additional Under Seat Storage Bin, Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear Suspension, Anti-cinch Seatbelts
Rear Brakes	Dual disc, 1-piston caliper	Color Choices	Firecracker Red
Park Brake Type	Independent, mechanical disc		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.