## **MULE PRO-FX™ 820 EPS**





\$15,099



TIMBERLINE GREEN



## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3,500 rpm

72.0 x 66.5mm **Bore x Stroke** 

**Compression Ratio** 9.5:1

DFI® with 34mm throttle body **Fuel System** 

75 amp

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

CAPABILITY

Rear Suspension /

Front Suspension /

**Wheel Travel** 

Double wishbone/8.5 in (L)/8.7 in (R)

Wheel Travel

Double wishbone/8.7 in

**Front Tires** 26 x 9-12, radial **Rear Tires** 26 x 11-12, radial

**Wheel Type** Allov

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt Steering

steering

**Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper **Park Brake Type** Independent, mechanical disc

7.9 gal

**Ground Clearance** 10.4 in

**Turning Radius** 16.0 ft

Cargo Bed

54.1 x 53.3 x 11.0 in **Dimensions (LxWxH)** 

**Cargo Bed Load** 

**Fuel Capacity** 

Capacity

999/600 lb CA Model

**Payload Capacity** 1,616.3/1,263.5 lb CA Model

**Seating Capacity** 

2,000 lb **Towing Capacity** 

Lighting (2) Halogen headlights

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.4 in

**Estimated Dry** 

Weight

1,757.4/1,759.6 lb\*\* CA Model

**Curb Weight** 

1,830.2/1,832.4 lb\* CA Model

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

**Color Choices** Timberline Green

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.