

2025

MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION



MSRP

\$21,899

METALLIC STARDUST WHITE



POWER		Fuel Capacity	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	Turning Radius	16.0 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Maximum Torque	61.5 lb-ft @ 4,500 rpm	Cargo Bed Load Capacity	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Bore x Stroke	92.0 x 75.1mm	Payload Capacity	1,616.3/1,263.5 lb CA Model
Compression Ratio	10.1:1	Seating Capacity	3-person (1 row), 6 person (2 row)
Fuel System	DFI® with 38mm throttle body	Towing Capacity	2,000 lb
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Lighting	(4) LED headlights
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	DETAILS	
Engine Braking	Yes	Overall Length	140.2 in
Alternator Output (max)	90 amp	Overall Width	64.0 in
CAPABILITY		Overall Height	80.9 in
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Estimated Dry Weight	1,955.8/1,958.0 lb** CA Model
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Curb Weight	2,030.8/2,033.0 lb* CA Model
Front Tires	26 x 9-12, radial	Wheelbase	92.3 in
Rear Tires	26 x 11-12, radial	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Wheel Type	Alloy	Additional Features	Roof, Additional Front Cup Holders, WARN® VRX 45 Winch, Premium Seats, Premium Shoulder Pads, Self-Leveling Rear Suspension, Quad LED Headlights, Brush Guard, Headlight Guards, Rear Bumper, Anti-cinch Seat Belts, Rearview Mirror, Additional Under Seat Storage Bin
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering	Color Choices	Metallic Stardust White
Front Brakes	Dual disc, 2-piston caliper		
Rear Brakes	Dual disc, 1-piston caliper		
Park Brake Type	Independent, mechanical disc		
Ground Clearance	12.6 in (max), 11.6 in (std)		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.