MULE PRO-MX™ EPS





MSRP \$14,099



GRAY



TIMBERLINE GREEN



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

695cc Displacement

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio

Fuel System DFI® with 44mm throttle body

35.7 amp

Continuously Variable Transmission (CVT) with **Transmission**

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

Ground Clearance

Park Brake Type

10.6 in

Fuel Capacity

Turning Radius 14.0 ft

Cargo Bed Dimensions

(LxWxH)

33.4 x 44.1 x 9.1 in

Independent, mechanical disc

Cargo Bed Load

Capacity

699 lb / 600 lb CA Model

Payload Capacity

1,200 lb / 1,100 lb CA Model

Seating Capacity

Towing Capacity

1,500 lb

9.5 gal

Lighting

(2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel**

Rear Suspension / Double wishbone/9.1 in **Wheel Travel**

Front Tires 25 x 8-12, radial

25 x 10-12, radial Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual disc, 2-piston caliper **Rear Brakes** Dual disc, 1-piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in

Overall Height 74.4 in

Curb Weight 1,587.6 lb* / 1,589.8 lb* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip

meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator

lamp, seatbelt reminder lamps

Color Choices Gray, Timberline Green

Scan with camera to view videos, key features and more.

Rear Tires



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.