MULE PRO-MX™ LE





\$14,699



DEEP BLUE



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Park Brake Type Independent, mechanical disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

33.4 x 44.1 x 9.1 in Cargo Bed **Dimensions (LxWxH)**

Cargo Bed Load

Capacity

699 lb / 600 lb CA Model

Payload Capacity 1,200 lb / 1,100 lb CA Model

Seating Capacity

Towing Capacity

1.500 lb

Lighting

(2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.6 in

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

Front Tires

25 x 8-12, radial

Rear Tires 25 x 10-12, radial

Electric Power Steering (EPS), Tilt steering **Steering**

Front Brakes Rear Brakes Dual disc, 1-piston caliper

Dual disc, 2-piston caliper

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,594.2 lb* / 1,596.4 lb* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

> fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Additional Features Roof, Cast Aluminum Wheels

Color Choices Deep Blue

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471