MULE PRO-MX™ SE





\$15,499



GOLD



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal **Transmission**

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

35.7 amp

Alternator Output

CAPABILITY

Front Suspension / Double wishbone / 8.6 in

Wheel Travel

Rear Suspension /

Wheel Travel

Double wishbone/9.1 in

Front Tires

25 x 8-12, radial 25 x 10-12, radial

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Park Brake Type Independent, mechanical disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb / 600 lb CA Model

33.4 x 44.1 x 9.1 in

Cargo Bed Load

Payload Capacity

Capacity

1,200 lb / 1,100 lb CA Model

Seating Capacity 2

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

DETAILS

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,622.9 lb* / 1,625.1 lb* CA Model

Wheelbase

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Additional Features Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels,

Painted Body Panels

Color Choices Gold





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471