

2025

MULE PRO-MX™ SE

Kawasaki

Let the Good Times Roll®

MSRP


\$15,499

 GOLD



| POWER | | Park Brake Type | |
|---------------------------------|---|------------------------------|---|
| Engine | 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled | Ground Clearance | 10.6 in |
| Displacement | 695cc | Fuel Capacity | 9.5 gal |
| Maximum Torque | 42.7 lb-ft @ 5,000 rpm | Turning Radius | 14.0 ft |
| Bore x Stroke | 102.0 x 85.0mm | Cargo Bed Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in |
| Compression Ratio | 10.3:1 | Cargo Bed Load Capacity | 699 lb / 600 lb CA Model |
| Fuel System | DFI® with 44mm throttle body | Payload Capacity | 1,200 lb / 1,100 lb CA Model |
| Transmission | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R) | Seating Capacity | 2 |
| Final Drive | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Towing Capacity | 1,500 lb |
| Engine Braking | Yes | Lighting | (2) Halogen headlights, (2) LED headlights |
| Alternator Output (max) | 35.7 amp | DETAILS | |
| CAPABILITY | | Overall Length | 110.0 in |
| Front Suspension / Wheel Travel | Double wishbone/8.6 in | Overall Width | 60.0 in |
| Rear Suspension / Wheel Travel | Double wishbone/9.1 in | Overall Height | 75.8 in |
| Front Tires | 25 x 8-12, radial | Curb Weight | 1,622.9 lb* / 1,625.1 lb* CA Model |
| Rear Tires | 25 x 10-12, radial | Wheelbase | 78.9 in |
| Steering | Electric Power Steering (EPS), Tilt steering | Instruments | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
| Front Brakes | Dual disc, 2-piston caliper | Additional Features | Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels, Painted Body Panels |
| Rear Brakes | Dual disc, 1-piston caliper | Color Choices | Gold |

Scan with camera
to view videos,
key features
and more.





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.