ALL-NEW 2025 NAV[®] 4e









160mm drum

Let the Good Times Roll

POWER

CAPABILITY

Front Suspension

Rear Suspension

Front Tires

Rear Tires

Wheel Type

Front Brakes

to view videos,

and more.

Steering

Air-cooled induction motor	
4.0 kW @ 5,200 rpm	
10.7 kW @ 2,000 rpm	
37.6 lb-ft @ 2,000 rpm	
19 mph	
Lead-acid battery (x6)	
8 V (x6)	
Up to 17.5 miles	
Approx. 10 hours (0-100%)	
Primary reduction gear with Forward/Neutral/Reverse	
2WD	
Yes	

Ground Clearance	7.3 in
Turning Radius	12.8 ft
Cargo Bed Dimensions (LxWxH)	31.0 x 40.3 x 0.9 in
Cargo Bed Load Capacity	150 lb
Payload Capacity	800 lb
Seating Capacity	4-person (2 row)
Towing Capacity	500 lb
Lighting	All-LED lighting

Ladder type, tubular steel

DETAILS

Frame

Rear Brakes

2WD		
Yes	Overall Length	114.6 in
	Overall Width	51.6 in
	Overall Height	77.2 in
MacPherson strut	Estimated Dry Weight	1,232.6 lb**
Leaf springs with hydraulic shock absorbers	Curb Weight	1,301.0 lb*
23 x 10-14	Wheelbase	79.9 in
23 x 10-14	Instruments	Forward/reverse/neutral indicator, hour meter, battery pack charge level, and turn signal indicator
14" aluminum	Additional Features	Roof, Full-color TFT Instrumentation, 6 cup holders, 4 USB
Rack-and-pinion	Additional reatures	ports, Fold-Flat rear seat, Rubber floor mats, KQR™ system
N/A		compatible
	Color Choices	Vibrant Blue

*Curb weight includes all necessary materials and batteries to operate correctly, and tool kit (if supplied).

**Dry weight does not include all necessary materials and batteries to operate correctly, and tool kit (if supplied).



This vehicle is designed and equipped to be used only on roadways designated for multi-use vehicles, such as personal transportation vehicles or golf carts. It is NOT designed for use on public roads.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. This vehicle is designed and equipped to be used only on roadways designated for multi-use vehicles, such as personal transportation vehicles or golf. ©2025 Kawasaki Motors Corp., U.S.A.

Equipment illustrated and specification may vary to meet individual markets.

Specifications subject to change. Visit Kawasaki.com for full product details.