

2025

# NINJA® 1100SX ABS



MSRP  
**\$13,699**

 METALLIC CARBON GRAY/METALLIC DIABLO BLACK



## POWER

<b>Engine</b>	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
<b>Displacement</b>	1,099cc
<b>Bore x Stroke</b>	77.0 x 59.0mm
<b>Compression Ratio</b>	11.8:1
<b>Maximum Horsepower</b>	134.0 hp <sup>1</sup> @ 9,000 rpm
<b>Maximum Torque</b>	83.2 lb-ft @ 7,600 rpm
<b>Fuel System</b>	DFI® with 38mm Electronic Throttle Valves
<b>Ignition</b>	TCBI with Digital Advance
<b>Transmission</b>	6-speed, return shift with wet multi-disc manual Assist & Slipper Clutch
<b>Final Drive</b>	Sealed chain
<b>Electronic Rider Aids</b>	Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	41mm inverted telescopic Showa fork with compression and rebound damping, adjustable spring preload/4.7 in
<b>Rear Suspension / Wheel Travel</b>	Horizontal back-link, gas-charged rear shock with rebound damping, remotely adjustable spring preload/5.6 in

<b>Front Tire</b>	120/70-17
<b>Rear Tire</b>	190/50-17
<b>Front Brakes</b>	Dual 300mm discs with radial-mount 4-piston monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
<b>Rear Brakes</b>	Single 260mm disc with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)

## DETAILS

<b>Frame Type</b>	Twin-spar aluminum
<b>Rake/Trail</b>	24.0° /3.9 in
<b>Overall Length</b>	82.7 in
<b>Overall Width</b>	31.7 in
<b>Overall Height</b>	46.9 in/48.2 in w/ windshield high
<b>Ground Clearance</b>	5.3 in
<b>Seat Height</b>	32.3 in
<b>Estimated Dry Weight</b>	471.9 lb**
<b>Curb Weight</b>	518.2 lb*
<b>Fuel Capacity</b>	5.0 gal
<b>Wheelbase</b>	56.7 in
<b>Special Features</b>	4.3" All-digital TFT Instrumentation, All-LED lighting, USB Type-C outlet, Smartphone Connectivity with available Voice Command via RIDEOLOGY THE APP MOTORCYCLE***
<b>Color Choices</b>	Metallic Carbon Gray/Metallic Diablo Black

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*\*RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

**Kawasaki**  
Let the Good Times Roll®