NINJA® ZX™-10RR ABS





MSRP **\$30,499**



METALLIC MATTE GRAPHENESTEEL GRAY



POWER

Engine 4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-

cooled

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 13.0:

Maximum 188.0

Horsepower

188.0 hp¹ @ 11,500 rpm

Maximum Torque 81.7 lb-ft @ 11,500 rpm

Fuel System DFI®, 47mm throttle bodies and Variable Air Intake

System (VAI)

Ignition TCBI with digital advance

Transmission 6-speed, return shift

Final Drive Sealed chain

Electronic Rider

Aids

Öhlins Electronic Steering Damper, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF), Power Modes

(Full/Mid/Low)

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Showa Balance Free Fork (BFF), adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in

Rear Suspension / Wheel Travel

Horizontal back-link with Showa Balance Free Rear Cushion (BFRC) lite shock, stepless, dual-range (low-/ high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire 120/70 ZR17

Rear Tire 190/55 ZR17

Front Brakes Brembo dual semi-floating 330mm discs with dual radial

mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 220mm disc with aluminum single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

DETAILS

Fuel Capacity

Frame Type

Rake/Trail

Overall Length

Overall Width

Overall Height

Ground Clearance

Seat Height

Aluminum perimeter

25.0°/4.1 in

82.1 in

46.7 in

5.3 in

32.9 in

Curb Weight 456.4 lb*

Wheelbase 57.1 in

Special Features 4.3" Full-Color TFT Instrumentation, Smartphone

Connectivity via RIDEOLOGY THE APP

Color Choices Metallic Matte Graphenesteel Gray

4.5 gal

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.