









TRUETIMBER® STRATA



POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	
Displacement	999cc	
Maximum Horsepower	92.0 hp1 @ 8,500 rpm	
Maximum Torque	65.8 lb-ft @ 5,500 rpm	
Bore x Stroke	73.4 x 59.0mm	
Compression Ratio	10.6:1	
Fuel System	EFI	
Ignition	TCBI with Digital Advance	
Starting System	Electric	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 4WD with locking rear differential, shaft	
Engine Braking	Yes	
Alternator Output (max)	85 amp	
Electronic Rider Aids	Power Modes, Economical Riding Indicator	

Ground Clearance	13.2/13.8 in (max preload); 13.2 in CA Model	
Fuel Capacity	12.9 gal	
Turning Radius	19.0 ft	
Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in	
Cargo Bed Load Capacity	1,000/600 lb CA Model	
Payload Capacity	1,444/1,290 lb CA Model	
Seating Capacity	6-person (2 row), bench seats	
Towing Capacity	2,500 lb	
Lighting	All-LED lighting	

DETAILS

	Selectable 4WD with locking rear differential, shaft	Frame	Ladder type, tubular steel
	Yes	Overall Length	155.3 in
	85 amp	Overall Width	64.0 in
5	Power Modes, Economical Riding Indicator	Overall Height	81.5 in
		Estimated Dry Weight	2,368.2/2,370.4 lb** CA Model
		Curb Weight	2,478.4/2,480.6 lb* CA Model
	Long-Travel, Double Wishbone/12.7 in	Wheelbase	122.2 in
Long-Tra	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery
	Duro 27 x 9-14		voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and
	Duro 27 x 11-14		warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
	14" Aluminum	Additional Features	Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-
	Rack-and-pinion w/ Electric Power Steering (EPS)		color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system
	Dual hydraulic 249mm discs with two-piston calipers		compatible
	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	TRUETIMBER® STRATA



CAPABILITY

Front Suspension / Wheel Travel Rear Suspension / Wheel Travel Front Tires Rear Tires Wheel Type Steering Front Brakes Rear Brakes



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.