2025 **RIDGE[®] HVAC**







POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	92.0 hp1 @ 8,500 rpm
Maximum Torque	65.8 lb-ft @ 5,500 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

Ground Clearance	12.6/13.8 in (max preload); 12.6 in CA Model	
Fuel Capacity	12.9 gal	
Turning Radius	15.0 ft	
Cargo Bed Dimensions (LxWxH)	34.6 x 49.0 x 12.8 in	
Cargo Bed Load Capacity	1,000/600 lb CA Model	
Payload Capacity	1,275/875 lb CA Model	
Seating Capacity	3, bench seat	
Towing Capacity	2,500 lb	
Lighting	All-LED lighting	

DETAILS

Final Drive Sel	electable 4WD with locking rear differential, shaft	Frame	Ladder type, tubular steel
Engine Braking Yes	25	Overall Length	124.4 in
Alternator Output 85 a (max)	5 amp	Overall Width	64.0 in
Electronic Rider Aids Pow	ower Modes, Economical Riding Indicator	Overall Height	81.3 in
		Estimated Dry Weight	1,940.4/1,942.6 lb** CA Model
CAPABILITY		Curb Weight	2,046.2/2,048.4 lb* CA Model
	ong-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in
Wheel Travel Rear Suspension / Lor Wheel Travel	ong-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator,
Front Tires Dur	uro 27 x 9-14		maintenance reminder, high beam, neutral, reverse, and
Rear Tires Dur	uro 27 x 11-14		warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Wheel Type 14"	" Aluminum	Additional Features	Full Cab with HVAC, Adjustable driver's seat, ERGO-FIT®, Full-
Steering Rac	ack-and-pinion w/ Electric Power Steering (EPS)		color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system
Front Brakes Dua	ual hydraulic 249mm discs with two-piston calipers		compatible
Rear Brakes Dua	ual hydraulic 249mm discs with single-piston calipers	Color Choices	Candy Persimmon Red





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.