2025 **RIDGE[®] RANCH EDITION**





METALLIC STARDUST WHITE



POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	
Displacement	999cc	
Maximum Horsepower	92.0 hp1 @ 8,500 rpm	
Maximum Torque	65.8 lb-ft @ 5,500 rpm	
Bore x Stroke	73.4 x 59.0mm	
Compression Ratio	10.6:1	
Fuel System	EFI	
Ignition	TCBI with Digital Advance	
Starting System	Electric	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 4WD with locking rear differential, shaft	
Engine Braking	Yes	
Alternator Output (max)	85 amp	
Electronic Rider Aids	Power Modes, Economical Riding Indicator	

CAPABILITY

Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Wheelbase	90.7 in
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery
Front Tires	Duro 27 x 9-14		voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil
Rear Tires	Duro 27 x 11-14		pressure, water temperature)
Wheel Type	Aluminum Additional Features		WARN® VRX 45 Powersport Winch, Adjustable driver's seat,
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Metallic Stardust White

Seating Capacity

Towing Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Estimated Dry Weight

Lighting

Frame





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.



3, bench seat

All-LED lighting

Ladder type, tubular steel

1,810.3/1,812.5 lb** CA Model

1,911.7/1,913.9 lb* CA Model

2,500 lb

126.4 in

64.0 in

81.9 in

